



Grab-and-Go Refrigeration

SERVING THE FOOD INDUSTRY SINCE 1951

24" Grab-and-Go Open Refrigerated Floor Self-Serve Display Case

ITEM: 25825

MODEL: RS-CN-0250



Display your products on the go with this slim unit, ideal for tight spaces.

This open refrigerated floor display case is the perfect for showcasing products in restaurants, cafés, and bakeries, where space is limited. Featuring a sleek, durable design, this unit offers excellent visibility and fits easily into compact spaces. Its open front and crystal-clear glass ensure products are easily seen and accessible to customers. Ideal for grab-and-go service, the unit features precise digital temperature controls to maintain safe and consistent cooling. Adjustable shelves provide flexibility to accommodate a variety of product sizes, and a pull-down curtain helps retain cold air when the case is not in use.

The unit uses eco-friendly R290 refrigerant for efficient cooling and features LED lighting to highlight products while saving energy. For convenience, the display case features casters and a sturdy stand for easy movement, installation, and cleaning, while also protecting floors and enhancing space flexibility.

FEATURES:

- Sleek & Durable Design
- Adjustable Shelves
- Pull down Curtain
- R290 Refrigerant
- LED Lighting System
- · Casters and Stand
- LED Lighting System
- 64.6 db during operation

Available in Canada only.

Telephone: 1-800-465-0234 Fax: (905) 607-0234

Email: sales@omcan.com

Website: www.omcan.com


















Grab-and-Go Refrigeration



FEATURES

Condenser located on the back, ensures sufficient space for air cooling



condenser fan motor built in front for easy access



Equipped with digital display, hidden casters & two adjustable feet



TECHNICAL SPECIFICATION	
Item	25825
Model	RS-CN-0250
Capacity	8.9 cu. ft. (252 L)
Number of Doors	1 Pull Down Curtain
Number of Shelves	3
Shelf Dimensions	20.8" x 11.2" / 530 x 284 mm 20.8" x 14" / 530 x 355 mm
Number of Casters	4
Power	1380 W
Lamp Power (LED)	10 W
Current	14.5 A
Electrical	110V / 60Hz / 1Ph
Temperature Controller	Digital
Temperature Range	2 - 10°C/36 - 50 °F
Refrigerant	R290
Injection	148g
Type Of Climate	6
Insulation Material	Cyclopentane
Defrosting	Automatic
Cooling System	Air Cooling
Interior Dimensions (WDH)	22" x 21.8" x 39"/ 571 x 556 x 993 mm
Net Weight	220.5 lbs/ 100 kgs
Net Dimensions (WDH)	24" x 29.7" x 67"/ 610 x 754 x 1704 mm
Gross Weight	243 lbs/ 110 kgs
Gross Dimensions (WDH)	27" x 33" x 74"/ 691 x 830 x 1875 mm
Plug Type	NEMA 5-20P

Grab-and-Go Refrigeration



TECHNICAL DRAWING

