



ELITE SERIES REFRIGERATION

SERVING THE FOOD INDUSTRY SINCE 1951

11.5 CU. FT. ONE-SWING DOOR REFRIGERATION

Model: VR12 Item 41217

Most energy efficient cooler in its category. Specifically designed for convenience stores

and supermarkets





Establishing a NEW STANDARD in the commercial refrigeration industry.

KEY FEATURES

• BMAD Refrigeration System

Ensures rapid and effective cabinet cool down and maintains consistent temperature range with minimum energy consumption

• Electronic Temperature Controller

Assures the optimal performance of the cooler, delivering product temperature ideal for consumption.

High Efficiency Glass Door

Equipped with double panel glass and low-e film to reduce condensation. Door hinge is equipped with a self-closing system to ensure the door closes safely, and returns to original position, without any damages.

LED Lighting System

Our LED system uses a fraction of the energy of regular fluorescent lights and requires no replacement for up seven years.

CFC and HFC Free Cyclopentane Foam

Eco-friendly, recyclable and high efficiency cabinet insulation.

Electronic Fan Motors

Enhances performance and efficiency. Uses only a fraction of the energy than industry standard shaded-pole motor requires. Longer lifespan fan motor.

Low Maintenance Condenser

Imbera's finless condenser designed to minimize maintenance. Drastically reduces Total Cost of Ownership. Prevents dust that blocks air flow, to save energy and extend the life of the compressor.










ELITE SERIES REFRIGERATION


11.5 CU. FT. SWING DOOR REFRIGERATION




PRODUCT DIMENSION



TOP VIEW





FRONT VIEW SIDE VIEW

ITEM NUMBER	41217
MODEL	VR12
DESCRIPTION	11.5 cu.ft. One-Swing Door Refrigeration
VOLUME	11.5 ft ³ / 328.2 liters
DOORS	1
SHELVES	4
SHELF SIZE	20 7/8" x 17 3/8" / 530mm x 440mm
CAPACITY	20 oz Total: 168 Front: 6 Gravity: 144 12 oz Total: 384

TEMPERATURE RANGE ENERGY CONSUMPTION ELECTRICAL CORD LENGTH HORSEPOWER AMPS

TECHNICAL SPECIFICATIONS

WEIGHT

INTERNAL DIMENSIONS (WDH) DIMENSIONS (WDH)

12 oz. - Total: 384 0°C - 7°C / 32°F - 44.6°F 2.390 kWh/day* 115 V / 60 Hz / 1 Ph 118" / 3000 mm 1/6 4.0 Gross: 183 lbs. / 83 kg. Crated: 187.4 lbs. / 85 kg. 21 7/8" x 18 5/8" x 49 7/8" / 555 x 472 x 1266mm

24 7/8" x 23 1/4" x 63 5/8"/ 632 x 590 x 1616mm

OPTIONS Gravity Kit Casters



NEMA

5 - 15 125 VAC / 15 AMP









MADE IN MEXICO





SHIPPED ON PALLET





VR 12



BMAD System (Low maintenance high performance). Dimensions rounded up to the nearest inch or milimeter. Specications subject to change without notice.

OMCAN INC.

ephone: 1-800-465-0234 Fax: (905) 607-0234 Email: sales@omcan.com Website: www.omcan.com

















^{*} Energy consumption based on ANSI/ASHRAE Standard 72-2005.