

Aurora Reach-In Refrigeration, Solid Door, Stainless Steel

ITEM:	59024	59026	59028
MODEL:	RE-CN-0021E-HC	RE-CN-0041E-HC	RE-CN-0067E-HC



29" wide
59024



54" wide
59026



81" wide
59028

Aurora stainless steel reach-in refrigeration - your ideal kitchen partner for storing food and ingredients.

Spacious reach-in freezer crafted with enduring quality. Sleek design using stainless steel material featuring high-efficiency components. This freezer is perfect for your restaurant, cafe, or bakery for storing pre-prepped ingredients and portions of your signature dishes, fries or proteins.

FEATURES:

- Incredibly Spacious - Adjustable Shelves**
 This unit is extremely spacious with a large cabinet with multiple adjustable shelves, thus maximizing your commercial kitchen space.
- Powerful, environmentally safe refrigeration system**
 Uses with R290 refrigerant to keep your ingredients and fully-prepared foods at safe frozen temperatures. The compressor is bottom mounted for energy efficiency, and also raises the bottom shelf, so all your frozen ingredients are within reach and you don't have to bend as much during loading and unloading.
- Digital Temperature Control**
 Easily adjust the freezer cabinet's temperature with the digital temperature controller. The clear LCD readout also helps keep track of the unit's temperature.
- Autodefrost System**
 This unit has an automatic defrost feature which eliminates the need to spend invaluable time in cleaning out the ice.

Telephone: 1-800-465-0234


Fax: (905) 607-0234

Email: sales@omcan.com

Website: www.omcan.com



WARRANTY
 2 YEARS PARTS AND LABOUR
 5 YEARS ON COMPRESSOR



Authorized Dealer

TECHNICAL SPECIFICATION

Features	29" wide with 20.6 cu.ft. (583 L) capacity	54" wide with 41.3 cu.ft. (1169 L) capacity	81" wide with 72 cu.ft. (2040 L) capacity
Item	59024	59026	59028
Model	RE-CN-0021E-HC	RE-CN-0041E-HC	RE-CN-0067E-HC
Capacity	20.6 cu. ft. (583 L)	41.3 cu.ft. (1169 L)	72 cu.ft. (2040 L)
Number of Doors	1 Swing Door - Solid Door	2 Swing Doors - Solid Door	3 Swing Doors - Solid Door
Self-Closing Door	Yes		
Material	Exterior - 430 Stainless Steel Interior - 304 Stainless Steel		
Number of Shelves	3	6	9
Shelf Capacity (kg/pc)	88.2 lb. (40 kg.)		
Shelf Material	Plastic Coated		
Number of Casters	Yes (4)		
Power	348 W	249 W	3/4 HP
Amps	3.6 A	3.8 A	9 A
Electrical	110-120V / 60Hz / 1Ph		
Temperature Controller	Digital		
Temperature Range	0.5 - 5°C (33 - 41°F)		
Refrigerant	R290		
Insulation Material	Cyclopentane		
Cooling System	Ventilated		
Defrosting	Automatic		
Interior Dimensions (WDH)	24.4" x 27.1" x 53.5" (620 x 688 x 1360mm)	49.4" x 27.1" x 53.5" (1255 x 688 x 1360 mm)	76.3" x 27.1" x 60.2" (1938 x 688 x 1530 mm)
Net Weight	282.2 lb. (128 kg.)	447.5 lb. (203 kg.)	617.3 lb. (280 kg.)
Net Dimensions (WDH)	29" x 32.2" x 82.5" (736 x 818 x 2095 mm)	54" x 32.2" x 82.5" (1371 x 818 x 2095 mm)	80.9" x 32.2" x 82.5" (2054 x 818 x 2095 mm)
Gross Weight	337 lb. (153 kg.)	553 lb. (251 kg.)	706 lb. (320 kg.)
Gross Dimensions (WDH)	31" x 35" x 85" (787 x 880 x 2159 mm)	57" x 35" x 85" (1435 x 880 x 2160 mm)	84" x 35" x 84" (2120 x 890 x 2120 mm)
Plug Type	NEMA 5-15P		

** This equipment is intended for indoor environment using where ambient temperature do not exceed 24°C(75°F) & 55% relative humidity*

TECHNICAL DRAWING (measurements are in mm)

