



DISHWASHER

SERVING THE FOOD INDUSTRY SINCE 1951

24-INCH UNDERCOUNTER HEAVY-DUTY DISHWASHER WITH 4.75 kW POWER

Item: 46563 Model: CD-KR-SU02

**HIGH PERFORMANCE,
HIGH-QUALITY UNDERCOUNTER
HEAVY-DUTY DISHWASHER**



FEATURES

- Maximum rack capacity of 40 racks per hour at 59°F incoming water
- Maximum rack capacity of 48 racks per hour at 140°F incoming water
- Stainless steel non-clogging wash and rinse impeller
- Automatic water fill; automatic start / stop
- 304L stainless steel for corrosion resistance
- Easily removable large capacity strainer

Product might not be exactly as shown.



WARRANTY

PARTS AND LABOR



Authorized Dealer

DISHWASHER

24-INCH HEAVY-DUTY DISHWASHER WITH 4.75 KW POWER



FEATURES OF PROGRAMMABLE CONTROLLER

- Maximizes washing efficiency and provides a clean environment
- Minimum required wash and rinse temperatures (pre-heating 80 minutes)
- Built-in electric heater with powerful rinse pump
- Constant pressure and temperature
- Pumped liquid detergent and rinse agent
- Automatic pumped drain

STANDARD FEATURES

- Raises incoming water 59°F (15°C) → 180°F (82°C) hot water sanitizing
- Variable time cycles (30~210 seconds)
- Maximum rack capacity of 48 racks per hour at 140°F incoming water
- Maximum rack capacity of 40 racks per hour at 59°F incoming water
- Automatic water fill; automatic start / stop
- 3 factory preset options (40/36/30 racks per hour, 90/100/120 seconds per cycle): 70 seconds powerful wash | 10 seconds dwell time | 10 seconds hot water rinse
- Stainless steel non-clogging wash and rinse impeller
- 304L stainless steel for corrosion resistance
- Easily removable large capacity strainer
- Solid state, integrated LED display controls with status indicators
- Low-noise and large output 1 HP washing pump
- Rotating rinse impellers (both upper and lower) feature 5 rinse nozzles each - easily removable and interchangeable for cleaning and inspection
- Door actuated start
- Service diagnostics
- Listed on US Patent



PRODUCT SPECIFICATIONS

ITEM	46563	VARIABLE TIME CYCLE	30 - 210 seconds
MODEL	CD-KR-SU02	CYCLE (SEC)	90 seconds
POWER	4.75 kW	1 CYCLE WATER CONSUMPTION	0.8 gal. / 3.0L
AMPS	24 Amps	HOT WATER TEMPERATURE	59°F (15°C) → 180°F (82°C)
WASH PUMP POWER	1 HP	ELECTRICAL	220V / 60Hz / 1Ph
MAXIMUM RACK CAPACITY	40 Racks / hr. at 59°F incoming water 48 Racks / hr. at 140°F incoming water	DIMENSIONS (DWH)	24.6" x 23.6" x 34.2"
		WEIGHT	227 lbs. / 103 kg.

OMCAN INC.

Telephone: 1-800-465-0234
Fax: (905) 607-0234
E-mail: sales@omcan.com
Website: www.omcan.com



Follow us to keep up to date with the latest news and offers



2020.E.O.E

DISHWASHER

TECHNICAL DRAWINGS WITH DETAILED DIMENSIONS



LEGENDS

DEEP	Door Open	41.5"
	Door Close	25.4"
ELECTRIC	A	32.5"
	a	5.5"
WATER	B	14.7"
	b	2.7"
DRAIN	C	32.7"
	c	4.6"

Ø = Electrical Supply Connection

220V/60/1 / 24Amp

Comes with 6 ft. (1.8 m) cord for direct connection

W = Fresh Water Connection


10 PSI - 40 PSI (0.7 kg / cm² - 2.8 kg / cm²)

Optimum water pressure - 15 PSI (1.0 kg / cm²)


Spry water hardness: 5 grains

D = Drain Hose Connection


Max. Height: 18" (457 mm)




TOP VIEW



FRONT VIEW



SIDE VIEW



REAR VIEW

OMCAN INC.

Telephone: 1-800-465-0234

Fax: (905) 607-0234

E-mail: sales@omcan.com

Website: www.omcan.com



Follow us to keep up to date with the latest news and offers



2020.E.O.E